

Revision History

Document Version	Update Content	Update Date
v1.0.0	Initial Issue	2026/6/10

W8130D

Dante Network Cabinet Speaker

Product Datasheet



KEY FEATURES

- Built-in 30W amplifier, 70Hz to 20KHz frequency range and 109dB max sound pressure level.
- Standard PoE (IEEE 802.3af/at) support or External power supply(DC 24V 2A).
- Features advanced Dante digital audio tech.
- Exceptional voice and music reproduction.

Specifications

Speaker	
Speaker component	1 x 6.5" Woofer+1 x 1" high frequency driver unit
Sensitivity	95dB/1m/1W
Max sound pressure level	109dB
Amplifier	Class D Amplifier
Rated power	DC: 8Ω 30W or PoE: af-8Ω 8W / at-8Ω 20W
Frequency range	70Hz~20KHz
Coverage Pattern	90°H 90°V, 60m²
Acoustics	Mono
Interface	
Interface	1x RJ45(POE)
	1x 6-pin 3.5mm Phoenix terminal (24V DC input)
Hardware Specifications	
Memory	128MB RAM, 256MB Flash
Power input	PoE IEEE802.3af/at standard adaptive or DC 24V-2A
Casing	Aluminum-Alloy Grille+ABS

Specifications

Color	Black
Weight	3.80KG
Dimension	300 x 215 x 195mm (11.81 x 8.46 x 7.68 in)
Mounting method	Wall mounted
Environmental	
Installation environment	Indoor
Operating temperature	-20°C- 50°C (-4°F - 122°F)
Storage temperature	-40°C- 70°C (-40°F - 158°F)
Humidity	10% - 95% RH Non-condensing

Frequency Response Curve

